

FILE NO: NTP/GC/1004 Product Name: Nanoman Glass + Ceramic SDS DATE: 01/2/24

SECTION 1: IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: Nanoman Glass + Ceramic

Synonyms: Nanoman Glass and Ceramic Sealant

Nanoman Glass and Ceramic Coating

Nanotech Products Pty Ltd (ABN 47 153 300 933) **Company Name:** Address: Unit 3, 40 Ricketts Rd, Mount Waverley 3149

Telephone: 1300 696 266

Business Hours 9:00am to 5:00pm, Monday to Friday

Other Names Not Applicable

Recommended Use: For coating of windows, glass, ceramic and porcelain to achieve a self cleaning / easy

cleaning surface.

SECTION 2: HAZARDS IDENTIFICATION

Hazard Statement H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation

H336 May cause drowsiness or dizziness





Precautionary Statement (Prevention)

P210 Keep away from heat/sparks/open flames/hot surfaces – no smoking

P233 Keep container tightly closed

P240 Ground/bond container and receiving equipment

P241 Use explosion-proof electrical/ventilating/lighting/..../equipment

P242 Use only non-sparking tools

P243 Take precautionary measures against static discharge P261 Avoid breathing dust/fume/gas/mist/ vapours/spray

P264 Washthouroughly after handling

P271 Use only outdoors or in a well-ventilated area

P280 Wear protective gloves/protective clothing/eye protection/face protection

Preautionary Statement (Response)

P303+P361+P353 If on skin or hair: remove/take off immediately all contaminated

clothing. Rinse skin with water/shower

P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position

comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P312 Call a POISON CENTER or doctor/physician if victim feels unwell P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for

extinction.

Precautionary Statement (Storage)

P403+P233+P235 Store in a well-ventilated place. Keep cool. Keep container tightly

closed.

P405 Store locked up.



Product Name: Nanoman Glass + Ceramic s

FILE NO: NTP/GC/1004 SDS DATE: 01/2/24

Precautionary Statement (Disposal)

P501 Dispose of contents/container to an approved waste disposal plant.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical

Characterisation

Ingredients: Name CAS Proportion Hazard Risk Symbol Phrase

2-Proponol 67-63-0 <50 Ethanol 64-17-5 >50

All other ingredients determined not to be hazardous.

SECTION 4: FIRST AID MEASURES

General Advice: Remove contaminated or saturated clothing

Inhalation: Remove victim from exposure. Take affected persons out into the fresh air. In case of

persistent discomfort seek medical attention

Ingestion: Have the mouth rinsed with water. Have the patient drink plenty of water in small sips. Do not

induce vomiting. Obtain medical attention.

Skin Contact: Wash off immediately with plenty of water. If swelling, redness, blistering or irritation occurs

seek medical advice.

Eye contact: Keeping eyelid open, immediately rinse thoroughly for at least 5 minutes using plenty of water

or, eye rinsing solution. Seek medical attention.

Notes to physician: If required, therapy of irritative effect. After absorbing large amounts of substance:

administration of activated charcoal. Acceleration of gastrointestinal passage.

SECTION 5: FIRE-FIGHTING MEASURES

Specific Measures: Caution: Use of water spray when fighting fire may be insufficient.

Small fire: use foam, dry chemical, CO2 or water spray.

Large Fire: Use foam, fog or water spray – Do not use water jets.

Specific Hazards: HIGHLY FLAMMABLE If safe to do so move undamaged containers from fire area. Cool

containers with water until well after fire is out. Avoid getting water inside containers.

Hazchem Code: 2YE

Precautions for

Firefighters

Wear respiratory protection equipment. Fully-encapsulated, gas tight suits should be

worn for maximum protection.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions: Protective clothing should be worn to prevent excessive skin contact.

Environmental Precautions:

Prevent liquid entering sewers. Do not allow to enter surface waters, storm drains, etc.

Small spills: Take immediate steps to stop and contain the spill. Caution should be excised regarding

personnel safety and exposure to be spilled material. Eliminate all sources of ignition and wear protective clothing. Absorb small spills onto paper towels and evaporate in a safe place

Flush the contaminated area with plenty of water.



Product Name: Nanoman Glass + Ceramic

FILE NO: NTP/GC/1004 SDS DATE: 01/2/24

Large spills:

Stop leak if you can do it without risk. Eliminate all sources of ignition and static; restrict access to area until completion of clean-up procedure. Wear adequate protective equipment, use self-contained breathing apparatus in confined poorly-ventilated areas. Large quantities should be absorbed on to sand, earth or non combustible absorbent material and removed to a safe area for disposal. Flush the contaminated area with plenty of water.

SECTION 7: HANDLING AND STORAGE

Handling and

Avoid contact with skin or in eyes. Do not inhale vapour or mist. Keep away from Storage:

sources of ignition - No smoking. Take measures to prevent the build-up of

electrostatic charge. Open and handle container with care. Keep away from open fire. Keep

away from heating sources. Keep away from sources of ignition

Conditions for safe

Hygienic Measures:

Footwear:

Storage:

Keep container tightly closed in a cool, dry and well-ventilated place away

from direct sunlight and other sources of heat or ignition. Store away from oxidising agents. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Always wash hand before smoking, eating or using the toilet. Wash contaminated clothing and

Safety boots in industrial situations is advisory. Foot protection should comply with AS 2210,

Check regularly for leakage.

Storage Regulations: Refer Australian Standard AS 1940 -2004 "the storage and handling of flammable and

combustible liquids".

2A flammable liquid. Storage class:

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

National Exposure Standard:	Name	CAS No	STEL mg/m3	ppm	TWA mg/m3	ppm
otanuaru.	Ispropanol Ethyl alcohol	67-63-0 64-17-5	500	1,230	400 1880	983 1,000
Other Exposure Information	The exposure value at the TWA is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week					
Appropraite Engineering Controls	In industrial situations maintain the concentrations values below the TWA. This may be achieved by process modification, use of local exhaust ventilation, capturing substances at the source, or other methods.					
Respiratory Protection:	Where ventilation is not adequate, respiratory protection may be required. Avoid breathing vapours or mists. Select and use respirators in accordance with AS 1716 – Respiratory Protective Devices and be selected in accordance with AS 1715 – Selection, Use and Maintenance of Respiratory Protective Devices.					
Eye Protection:	The use of a face shield, chemical goggles or safety glasses with side shield protection as appropriate. Must comply with Australian Standards AS 1337 and be selected and used in accordance with AS 1336.					
Skin Protection:	Hand protection should comply with AS 2161, Occupational protective gloves – Selection Use and Maintenance. Recommendation: PVC, neoprene or nitile rubber gloves.					
Other Protective Clothing Equipment:	Impermeable clothing. Final choice of personal protective equipment will depend on individual circumstances and/or according to risk assessments undertaken.					

other protective equipment before storing or re-using.

occupational protective footwear- Guide to selection, care and use.



Product Name: Nanoman Glass + Ceramic

FILE NO: NTP/GC/1004 SDS DATE: 01/2/24

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Form: Liquid

Appearance: Colourless

Odor: Alcoholic, mild

Melting Point: N/A

Boiling Point: 82-83°C

Solubility in Water: fully miscible

Flash Point: 12 °C

Vapor Pressure: 42 hPa at 20 °C

Specific Gravity: 0.785 - 0.786 g/cm³ at 20 °C

Relative Density: 0.822 kg/l (at 20°C)

Ignition Temp. ca. 425 °C

Evaporation Rate: 0.300 (n=BuAc = 1)

Explosion Limits: lower: 2,0 Vol-% upper: 12,0 Vol-%

pH (500 g/I H₂O): n.a

Dynamic viscosity: 1 mPa.s (at 20°C)

Kinematic viscosity 1 mm²/s (at 20°C)

Volatile Organic

Compounds (VOC): 99.57% 818.426g/l

SECTION 10: STABILITY AND REACTIVITY

Chemical Stability: Stable under normal use conditions

Conditions to Avoid Heat, sparks, flame and build up of static electricity.

Incompatibility (Material

To Avoid): acids, alkalines, oxidants, reductants

Hazardous

Decomposition does not decompose with normal use

SECTION 11: TOXICOLOGICAL INFORMATION

General: From our experience and the information provided to us this product does present any

adverse health effects if the product is handled in accordance with this Material Safety Data

Sheet and product label.

Ingestion: May cause nausea, vomiting, headache, dizziness and gastric irritation

Eye Contact: May cause irritation and watering. High concentration of vapours may cause irritation.



FILE NO: NTP/GC/1004 Product Name: Nanoman Glass + Ceramic SDS DATE: 01/2/24

Skin Contact: Contact with the skin may result in irritation

Inhalation: Where the material is used in a poorly ventilated area, at elevated temperature or in confined

spaces, vapour may cause irritation to the mucous membranes of the respiratory tract. May

cause headaches, dizziness and nausea.

SECTION 12: ECOLOGICAL INFORMATION

Ecological No ecological problems are expected to occur when the product is handled and used with

Information: due care and attention

Avoid contaminating waterways **Ecotoxicity:**

SECTION 13: DISPOSAL CONSIDERATIONS

Whatever cannot be saved for recovery or recycling should be disposed of according **Disposal**

Considerations to relevant local authority, state and federal government regulations.

SECTION 14: TRANSPORT INFORMATION

	Land Transport	Sea Transport (IMDG / IMO)	Air Transport (IATA / ICAO)
UN Number	1987	1987	1987
Proper Shipping Name	Ethanol Solution / Mixture	Ethanol Solution / Mixture	Ethanol Solution / Mixture
DG Class	3	3	3
Identification Number of	33	33	33
Hazard			
Hazchem Code	2YE	2YE	2YE
Packaging Group	II	II	II
Marine pollutant	no	no	no

SECTION 15: REGULATORY INFORMATION

Classification: Highly Flammable

Poisons Schedule: Not scheduled

SECTION 16: OTHER INFORMATION

DISCLAIMER: The information contained in this Safety Data Sheet (SDS) is believed to be correct and was obtained from sources we believe are reliable. However, since data, safety standards and government regulations are subject to change and the conditions of handling and use, or misuse are beyond our control, we make no warranty either expressed or implied, with respect to the completeness or accuracy to the information contained herein. Nanotech Products makes no representations, guarantees or warranties of any kind as to the accuracy, suitability for particular applications, hazards connected with the use of the material, or the results to be obtained from the use thereof. User assumes all risks and liability of any use, processing or handling of any material, variations in methods, conditions and equipment used to store, handle or process the material and hazards connected with the use of the material are solely the responsibility of the user and remain at their sole discretion. Compliance with all applicable federal, state, and local laws and regulations remains the responsibility of the user, and the user has the responsibility to provide a safe work place, to examine all aspects of its operation and to determine if or where precautions, in addition to those described herein, are required.